



Description

The EU5500/L allows extension of the TCS 5500 digital conference system to accommodate a higher number of interpreter units.

Furthermore it creates a level of redundancy. In total 4 loops can be created with one extension unit.


Several extension units can be daisy-chained allowing a virtually unlimited number of devices connected.

Controls and Features

- Reset button
- 14 Indicator LEDs for system clock, port activity, power supply, external and info line activity
- 8 DIL Switches + associated indicator LEDs for (de-) activation of the power supply on each branch individually
- One rotary BCD Switch, for ID setting adjustment of extension unit
- One fuse (power supply)

Connectivity

- Eight 8-pin RJ-45 connectors for connection of 4 loops.
- Two 8-pin RJ-45 connectors for connection from CPU5500 or previous Extension Unit (IN & OUT)
- Two 8-pin RJ-45 connectors for connection to CPU5500 clock generator (IN and OUT)
- One Phoenix connector for 48V Power Supply



Accessoires

- Fully assembled Power Supply Cable, ready for use:
PW2 2m (71.67.4102)
(One power supply cable included in the delivery)

Specifications

Technical Data	
Dimensions (mm)	43 (h) x 483 (w) x 182 (d)
Weight (g)	+/- 2.300
Colour	RAL7021 (Matt Black)
Housing	Metal
Part Number	71.61.5051

