

IM-WCC-M

iMedia Wall Plate Computer Center

Crestron's iMedia provides an extremely simple and affordable multimedia presentation control solution for small conference rooms and training rooms. No comparable solution comes close to matching iMedia's speed and ease of installation, intuitive operation, and network manageability at such an incredibly low cost.

The iMedia Transport

The iMedia transport utilizes a single CAT5e* type cable to transmit computer RGB, video, and stereo audio signals to a single projector or plasma display. A typical XGA signal (1024 X 768 pixels at 60Hz) can be transmitted up to 84 feet using iMedia, while higher resolutions up to 1600 x 1200 can be handled over shorter distances. Audio is transmitted digitally at 20-bit, 48 kHz resolution. Control and power signals are also contained on the same wire, eliminating the need for separate control or power cables.

Wall Plate Computer Interface

The IM-WCC-M is an iMedia (IM) transmitter designed to install in a standard 2-gang electrical box, providing RGB and stereo audio inputs for connection to the output of a computer source. Installing wiring for the IM-WCC-M is extremely simple requiring just a single CresCAT-IM cable. Up to three IM-WCC-M's, or other IM transmitters, may be installed as part of a complete system to provide multiple input locations within the room.

Foolproof Operation

Every iMedia system is easy and intuitive to use. A single press of the large SELECT button on the face of the IM-WCC-M lowers the screen or lift, turns on the projector (or plasma, etc.) and routes the connected computer signal to the appropriate input. The front panel volume control affords easy adjustment of the audio level for the computer input. When used with an IM-RXV-M series receiver, the system's microphone level can be adjusted by holding the SELECT button and turning the VOLUME knob. The entire system can be turned off at any time by simply holding the SELECT button for 5 seconds.

For systems having more than one IM transmitter, selecting an input at a given input location overrides the previously selected input at any other location. The audio level for each input location is controlled individually by its respective volume control.

- > A simple, affordable wall plate computer interface
- > Streamlined user controls for foolproof operation
- > iMedia Transport for fast and easy single-cable installation
- > Supports XGA resolution up to 84 feet, UXGA maximum up to 34 feet
- > Provides microphone level control for IM-RXV-M series receivers
- > Complete system setup in minutes using iMedia Wizard Software



SPECIFICATIONS

RGB

Gain: 0dB (75 ohm termination)

Formats: RGBHV, RGBS, or RGsB

Resolution: 1024 x 768 @ 60Hz with maximum cable length of 84 feet, 1600 x 1200 @ 60Hz with maximum cable length of 34 feet; see manual for other resolutions

Audio

A-D Conversion: 20-bit, 48 kHz

Frequency Response: 20Hz to 20kHz ± 1 dB

Connectors - Front Panel

COMPUTER: (1) DB15HD female, RGB(VGA) input;

Formats: RGBHV, RGBS, RGsB;

Input Impedance: 75 ohms;

Sync Impedance: 1k ohms;

Maximum Input Level: 1 Vp-p;

Maximum Sync Level: 5 Vp-p

AUDIO: (1) 3.5mm TRS mini phone jack;

Unbalanced stereo line-level audio input;

Maximum Input Level: 2 Vrms;

Input Impedance: 10k ohms

Connectors - Rear Panel

IM: (1) 8-wire RJ45 female, iMedia output port;

Connects to IM input port of an iMedia receiver via CresCAT-IM cable*

Ground: (1) flying lead, green, chassis ground wire

Controls & LED Indicators

VOLUME: (1) Rotary knob, adjusts audio level for local input

SELECT: (1) Momentary pushbutton with green LED;

Momentary press initiates "system power on" command and selects local COMPUTER input; press and hold for 5 seconds or more initiates "system power off"; press, hold and turn VOLUME adjusts system microphone level

IM-WCC-M iMedia Wall Plate Computer Center

Power Requirements

Power is provided by the IM receiver via the IM transport

Environmental

Temperature: 41° to 104°F (5° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Enclosure

2-gang wall plate, mountable in a 2.5 in (6.35 cm) deep electrical box;

Note: Conduit must enter box via top or bottom knockouts only

Dimensions

Height: 4.50 in (11.43 cm)

Width: 4.56 in (11.59 cm)

Depth: 2.81 in (7.13 cm)

Weight

0.85 lb (0.39 kg)

** For iMedia use CresCAT-IM cable, or quality CAT5e/CAT6 cable having a maximum delay skew of 15nS per 100m.*

Available Models

IM-WCC-M: iMedia Wall Plate Computer Center w/Mic Control

Available Accessories

CRESCAT-IM-P-DRN-SP1000: iMedia Cable, Low-skew CAT5e w/drain wire for iMedia and QuickMedia, plenum, 1000 ft spool

CRESCAT-IM-P-DRN-SP500: iMedia Cable, Low-skew CAT5e w/drain wire for iMedia and QuickMedia, plenum, 500 ft spool

IM-WCC-M iMedia Wall Plate Computer Center

